




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>F01N 3/28, 3/02, F02M 25/07</b>		<b>A1</b>	(11) International Publication Number: <b>WO 99/09307</b>
			(43) International Publication Date: 25 February 1999 (25.02.99)
(21) International Application Number: PCT/GB98/02408		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 10 August 1998 (10.08.98)			
(30) Priority Data: 9717034.4 13 August 1997 (13.08.97) GB			
(71) Applicant (for all designated States except US): JOHNSON MATTHEY PUBLIC LIMITED COMPANY [GB/GB]; 2-4 Cockspur Street, Trafalgar Square, London SW1Y 5BQ (GB).			
(72) Inventors; and (75) Inventors/Applicants (for US only): ALLANSSON, Ronny [SE/SE]; Alafors 6042, S-434 96 Kingsbacka (SE). ANDREASSON, Klas, Anders [SE/SE]; Traneredsv. 60A, S-426 77 V. Frolunda (SE). MYERS, Nils [GB/SE]; Nye-brostiten 52, S-443 30 Lerum (SE). UUSIMAKI, Ari [SE/SE]; Rantmastaregatan 20A, S-416058 Goteborg (SE). WARREN, James, Patrick [GB/GB]; 67 Burnside, Cambridge CB1 3PA (GB).			
(74) Agent: WISHART, Ian, Carmichael; Johnson Matthey Technology Centre, Blounts Court, Sonning Common, Reading RG4 9NH (GB).		Published With international search report.	

(54) Title: IMPROVEMENTS IN EMISSIONS CONTROL



## (57) Abstract

A heavy duty diesel engine (1) has an exhaust system incorporating a catalyst (5a) to convert NO to NO<sub>2</sub> and a particulate trap (5b) on which soot particles are continuously oxidised, and a portion of the cleaned gases are recirculated through a cooler (7) and an exhaust gas flow valve (8) before being mixed with air and fed to the engine cylinders. Considerable reductions in NO<sub>x</sub> can be achieved.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## IMPROVEMENTS IN EMISSIONS CONTROL

The present invention concerns improvements in emissions control. More especially, the invention concerns improvements in the control of NO<sub>x</sub> from diesel engines.

5

The use of emission control catalysts for engine exhaust clean-up is well established. Diesel engines have different characteristics from gasoline-fuelled engines, with a different mix of pollutants caused by the different fuels, the different combustion characteristics in each engine and the lower temperatures met with in exhausts from diesel engines. Additionally, diesel engines emit more noticeable particulates, especially under heavy load and upon start-up, than gasoline engines. In general, it can be said that diesel engines emit less NO<sub>x</sub> than a gasoline engine under most conditions, but because diesel engines mostly or exclusively operate on a high air to fuel ratio, that is are "lean"-burn engines, the chemistry of the exhaust gas does not favour NO<sub>x</sub> reduction, because of the excess of oxidising species.

15

To meet the various emission regulations already or about to enter force, it has become necessary to treat diesel exhausts in various ways. Oxidation catalysts, which catalyse the oxidation of unburnt hydrocarbons ("HCs") and carbon monoxide ("CO") are now regularly fitted to light duty diesels, and particulate traps of various types are becoming commonplace on heavy duty diesels as used in trucks, buses and some stationary engines. A technique for improving exhaust gas emissions, especially NO<sub>x</sub> emissions from diesel engines is exhaust gas recirculation ("EGR"), which takes a proportion of the exhaust gas and recirculates it into the engine cylinders. Generally, about 30 to 60vol% of the exhaust gases are recirculated, depending upon the characteristics of the particular engine and the emission limits which must be met. Although EGR has been used with gasoline engines for about ten years, it has only been more recently fitted to diesel engines; we believe that most vehicles currently fitted with EGR are passenger car light duty diesel engines. In the case of engines fitted with a catalyst, the exhaust gas is always taken from upstream of the catalyst. It is generally expected that EGR would have a significant effect on emissions from heavy duty diesel engines, that is those fitted to heavy trucks and buses. Because of the engineering problems caused by the very different exhaust characteristics compared to light

30

duty diesel engines, however, this has proved difficult to achieve. In particular, there is no commercial source of an EGR valve of suitable size and materials to be fitted to a heavy duty diesel engine.

5           We refer also to a device marketed as the "CRT" by Johnson Matthey PLC. This device is described in US Patent No 4,902,487 and is a continuously regenerative particulate trap. Unlike the vast majority of particulate traps, however, this device regenerates *in situ* without the need for periodic replacement or electrical heating to ignite the soot. Such device relies upon a catalyst system which generates NO<sub>2</sub> which we found is effective to  
10       cause low temperature combustion of trapped soot particles.

          The principle of the CRT has been adopted by Hino in their published Japanese patent applications JP 8338320 and JP 9088727, in combination with EGR. However, such systems as described are not believed to be capable of use in true heavy duty diesel  
15       applications.

          We have surprisingly found that a novel diesel engine system can offer very low levels of NO<sub>x</sub>. The present invention provides a diesel engine system comprising a diesel engine and an exhaust system therefor, characterised in that the exhaust system incorporates  
20       a catalyst effective to convert NO to NO<sub>2</sub> under normal operating conditions, a trap for particulates mounted downstream of the catalyst and an exhaust gas recirculation system mounted downstream of the trap and cooling means to cool the portion of exhaust gas which is recirculated.

25           The invention also provides a process for the reduction of NO<sub>x</sub> in diesel engine exhaust gases, comprising, in order, converting at least a portion of the NO in the gases to NO<sub>2</sub> by passing the gases over a catalyst, trapping at least the majority of carbonaceous particles in the gases on a trap and continuously oxidising said particles and cooling and recirculating at least a portion of the cleaned gases leaving the trap, to the engine cylinders.

30

The exhaust gas recirculation may be carried out using essentially well established technology, using valves in the exhaust system and a control system. It is believed that the present invention may be operated most effectively at a lower recirculation ratio (eg 5 to 30% by vol) than is normal. Although engine intake vacuum may provide adequate EGR, it may be preferable to provide pumping to provide a vacuum using a variable speed fan or pump operating under the control of the engine management unit.

The catalyst and trap may be as described in USP 4,902,487 or as practised in the commercial Johnson Matthey CRT device. A preferred trap is an extruded ceramic, eg cordierite, wall flow filter.

It is to be realised that since only a portion of the exhaust gases is recycled, the system and process of the invention may be operated in one embodiment so that such a portion of the exhaust gases leaving the engine is treated by the catalyst and trap and all the treated portion is recirculated. The remainder of the exhaust gases is passed into a conventional exhaust system which may desirably contain a separate catalyst and trap combination.

The present invention is believed to offer, in its preferred embodiments, certain unexpected advantages. The invention, because it does not depend upon a reduction catalyst reaching light-off temperature, is effective to reduce NO<sub>x</sub> at all engine operating temperatures. Additionally, traditional EGR systems suffer from wear and other degradation both of the EGR valves which are used to extract the recirculating portion of the exhaust gases, and on engine or exhaust components themselves. Such degradation may lead to expensive rebuilds, and a system that offers the potential for savings in this area has considerable economic value. In particular, the reduction in soot provides relatively clean gas for the cooling means. The main benefit of this is the maintenance of good heat exchange compared to a heavily sooted cooling means, but other consequences include reduced servicing requirements.

In accordance with the principles of the present invention, the skilled person may adapt the invention to different diesel engines and in different ways achieve the benefits of the invention.

5           The present invention is illustrated with reference to the accompanying schematic drawing of one embodiment of the invention.

A heavy duty diesel engine is generally indicated by 1. The engine exhaust manifold, 2, connects to a turbine, 3, and feeds into an exhaust system, 4. A standard commercial  
10 Continuous Regenerating Trap, 5, obtainable from Johnson Matthey PLC, Royston, England, is fitted in the exhaust system, and includes a catalyst element, 5a, and a filter element, 5b. Mounted downstream of the CRT, is a simple T-junction pipe, 6, which can extract a portion of cleaned exhaust gas, according to the status of the exhaust flow valve described below. The portion of exhaust gas is passed to an exhaust gas cooler, generally indicated by 7,  
15 which is effective to reduce the temperature of the exhaust gas to the range 80 to 150°C. The exhaust gas cooler may be a liquid-cooled device, as shown in the drawing, or air cooled. The cooled gas then passes through an exhaust gas flow valve, 8, which is actuated under the control of an engine management unit (not shown). According to the position of the valve (in the particular test reported below, shut = no EGR, fully open = 30% EGR),  
20 exhaust gas is extracted through pipe 6 for recirculation. The engine management unit utilises conventional sensing to determine suitable load conditions for EGR operation, for example at idle and up to about half load conditions, including acceleration, but the use of EGR under full load conditions is not presently expected to be advantageous.

25           The exhaust gas is then blended with fresh air for combustion taken through an air intake, 9. Desirably an inter-cooler unit, 10, cools the combustion air and recycled exhaust gas to about 25 to 40°C before it is compressed by a turbocharger unit, 11, driven by a shaft from the turbine, 3. The charge of gas is then passed through the standard inter-cooler unit, 12, to cool the gas to about 35 to 60°C before it is fed to the engine.

The invention will also be described for illustrative purposes only in the following Example.

### **EXAMPLE**

5

A heavy duty 10 litre diesel bus engine (manufactured by Volvo) was used for a series of tests, using the configuration shown in Figure 1.

10 The reduction of NO<sub>x</sub> at the tailpipe, relative to the normal output of the engine, was plotted on Figure 2 at various EGR rates. (The prototype valve could not be closed entirely and even in the nominally fully closed position provided about 1% EGR. It can readily be seen that even at 5% EGR, there is an approximately 15% reduction in tailpipe NO<sub>x</sub> emissions. At EGR rates of 25 to 30%, the reduction of NO<sub>x</sub> is 80 to 90% or more. Use of EGR does, however, incur a fuel penalty shown in a broken line on Figure 2. Beyond 30%  
15 EGR, this penalty becomes unacceptable.

The results shown in Figure 2 represent 50% load (585Nm) at an intermediate speed (1450 rpm), which is equivalent to ECE Regulation 49 mode #4.

20 Further tests were carried out under different load/engine speed combinations according to the various modes of ECE R-49. In all cases there was a considerable and unexpected reduction in NO<sub>x</sub>, increasing with EGR rate. The system tested was not optimised, yet promises NO<sub>x</sub> reductions of 70% or more. It is believed that a conventional EGR, operating at much higher EGR rates than in the present invention, *eg* 30 to 50%, does  
25 not offer NO<sub>x</sub> reductions greater than 60%.


**CLAIMS**

1. A diesel engine system comprising a diesel engine and an exhaust system therefor, characterised in that the exhaust system incorporates a catalyst effective to convert NO to NO<sub>2</sub> under normal operating conditions, a trap for particulates mounted downstream of the catalyst, an exhaust gas recirculation system mounted downstream of the trap and cooling means for the portion of exhaust gas that is recirculated.
2. A system according to claim 1, wherein said exhaust gas recirculation system comprises a valve and a control system therefor, and the cooling means is mounted upstream of the valve.
3. A system according to claim 1 or 2, wherein the exhaust gas recirculation ratio is adjustable in the range 5 to 30% by vol according to the position of the valve.
4. A system according to claim 1, 2 or 3, wherein a pump is incorporated in the exhaust gas recirculation system, said pump operating under the control of an engine management system.
5. A system according to any one of the preceding claims, wherein the diesel engine is a heavy duty diesel engine.
6. A process for the reduction of NO<sub>x</sub> in diesel engine exhaust gases, comprising, in order, converting at least a portion of the NO in the gases to NO<sub>2</sub> by passing the gases over a catalyst, trapping at least the majority of carbonaceous particles in the gases on a trap and continuously oxidising said particles and cooling and recirculating at least a portion of the cleaned gases leaving the trap to the engine cylinders.
7. A process according to claim 7, wherein the quantity of exhaust gas recirculated is in the range 5 to 30% by vol.




8. A process according to claim 7 or 8, wherein the portion of exhaust gas recirculated is cooled before it meets an exhaust gas recirculation valve.

1/2



2/2



# INTERNATIONAL SEARCH REPORT

International Application No

/GB 98/02408

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 F01N3/28 F01N3/02 F02M25/07

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 F01N F02M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	<p>US 4 902 487 A (JOHNSON MATTHEY INC)  20 February 1990  cited in the application  see column 1, line 66 - column 2, line 52  see column 3, line 21-35  see column 3, line 52 - column 4, line 5  see figure 1</p> <p style="text-align: center;">--- -/--</p>	1,2,6,8



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

### Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

S' document member of the same patent family

Date of the actual completion of the international search

26 November 1998

Date of mailing of the international search report

08/12/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Klinger, T

# INTERNATIONAL SEARCH REPORT

ional Application No

T/GB 98/02408

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	<p>DATABASE WPI  Section Ch, Week 9710  Derwent Publications Ltd., London, GB;  Class H06, AN 97-104299  XP002085831  &amp; JP 08 338320 A (HINO MOTORS LTD)  , 24 December 1996</p>	1,2,6,8
A	<p>see abstract  &amp; PATENT ABSTRACTS OF JAPAN  vol. 97, no. 4, 30 April 1997  &amp; JP 08 338320 A (HINO MOTORS CO),  24 December 1996  see abstract; figure 9  -----</p>	5

# INTERNATIONAL SEARCH REPORT

tion on patent family members

onal Application No

/GB 98/02408

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4902487 A	20-02-1990	AT 132940 T	15-01-1996
		DE 68925382 D	22-02-1996
		DE 68925382 T	15-05-1996
		DK 233389 A	14-11-1989
		EP 0341832 A	15-11-1989
		ES 2081301 T	01-03-1996
		GR 3018800 T	30-04-1996
		IE 71167 B	29-01-1997
		JP 1318715 A	25-12-1989

---